

**IN THE CLAIMS:**

Claims 1-2 (Canceled)

3. (Previously Presented) A sealant-containing tire with an annular sealant chamber formed at an inner surface of a tread of a tire body, and with the inside of the sealant chamber being filled with sealant,

wherein said sealant-containing tire comprises:

an outer liner directly fastened to the inner surface of a side wall of the tire body;  
and

an inner liner with left and right ends directly fastened to the inner surface of the outer liner so that a sealant chamber is defined between a central part of the inner liner and the inner surface of the tread, said sealant chamber containing the sealant, which sealant directly contacts the tread,

wherein the inner liner and the tire body are composed of materials having anti-sticking properties.

4. (Previously Presented) A sealant-containing tire with an annular sealant chamber formed at an inner surface of a tread of a tire body, and with the inside of the sealant chamber being filled with sealant,

wherein said sealant-containing tire comprises:

a first outer liner directly fastened to the inner surface of the tread of the tire body;

a second outer liner directly fastened to the inner surface of a side wall of the tire body; and

an inner liner with left and right ends fastened to the inner surface of the second outer liner so that a sealant chamber is defined between a central part of the inner liner and the inner surface of the first outer liner,

wherein the first outer liner and the inner liner are composed of materials having anti-sticking properties.